

| Technical data                                       |    |                                             |     |     |     |      |      |      |      |      |      |      |      |
|------------------------------------------------------|----|---------------------------------------------|-----|-----|-----|------|------|------|------|------|------|------|------|
| Typ                                                  |    | 500                                         | 600 | 650 | 700 | 800  | 900  | 1000 | 1100 | 1200 | 1400 | 1600 | 1800 |
| <b>Rotary table diameter</b>                         | mm | 512                                         | 584 | 656 | 728 | 800  | 904  | 1002 | 1120 | 1210 | 1410 | 1610 | 1810 |
| <b>Tie-bar clearance<br/>Minimum dimensions</b>      | mm | 355                                         | 405 | 460 | 500 | 560  | 630  | 710  | 780  | 890  | 1000 | 1120 | 1280 |
| <b>X</b>                                             | mm | results after selection of the media supply |     |     |     |      |      |      |      |      |      |      |      |
| <b>Y</b>                                             | mm | 125                                         | 125 | 125 | 125 | 125  | 160  | 160  | 160  | 160  | 160  | 160  | 220  |
| <b>Z</b>                                             | mm | 128                                         | 128 | 128 | 128 | 148  | 148  | 160  | 160  | 188  | 228  | 258  | 328  |
| <b>Rotary table, weight</b>                          | kg | 250                                         | 300 | 400 | 500 | 700  | 1000 | 1300 | 1400 | 2200 | 3100 | 4500 | 6600 |
| <b>Maximum mold weight<br/>on ejector side</b>       | kg | 450                                         | 500 | 600 | 800 | 1200 | 1600 | 2200 | 2800 | 3500 | 5000 | 6500 | 8000 |
| <b>Maximum number of media<br/>circuits possible</b> |    | 5                                           | 5   | 5   | 5   | 5    | 9    | 9    | 9    | 9    | 9    | 9    | 9    |